



QDriver™ 60W

LED Power Supply



ATG ELECTRONICS



ATG Electronics® QDriver™ 60W LED Power Supply is a universal device that operates on input voltage ranging from 85 VAC~264VAC, and provides 5 amperes of filtered and regulated 12VDC power (nominal) or 2.5 amperes of 24VDC power (nominal) to LED lighting fixtures, controllers or decoders etc.

QDriver™ 60W comes with a 1.5 meter (4.92 feet) long power cord with American plug or European plug to suit different interface. It also has a 1.5 meter (4.92 feet) long cable, which can directly attach to ATG Electronics products or via power adaptor board.

QDriver™ 60W is contained in a compact plastic housing and applicable for dry environment.

QDriver™ 60W is the ideal and cost effective solution for driving a small quantity of 12VDC or 24VDC LED lighting fixtures, controllers or decoders etc. It has successfully been installed with thousands of LED lighting systems in the world.

ATG
Electronics Corp.

Light your world
Color your life!

Features

- Direct Assembly on DIN-Rail.
- Enclosed and compact housing.
- Overload protection, constant current limiting.
- Short-circuit proof, 100% full load burn-in test.
- Built-in EMI filter, low ripple noise.
- Plug is available for North America, Europe etc.
- Simple primary hook-ups, class 2 outputs.
- No minimum load, no load balancing and no dip switches.
- Proven reliability at low cost.

Part Numbers

Part Number	Description	Unit
HPS-12060-000000-H1	60W, 12VDC 5A, 120VAC input	pcs
HPS-12060-000000-H2	60W, 12VDC 5A, 240VAC input	pcs
HPS-24060-000000-H1	60W, 24VDC 2.5A, 120VAC input	pcs
HPS-24060-000000-H2	60W, 24VDC 2.5A, 240VAC input	pcs

Technical Specifications

Part Number	HPS-12060-000000-H1 HPS-12060-000000-H2	HPS-24060-000000-H1 HPS-24060-000000-H2
Input Voltage	85 VAC~264VAC	85 VAC~264VAC
Input frequency	47 Hz ~63Hz	47 Hz ~63Hz
Output Voltage	12VDC	24VDC
Output Current	5A	2.5A
Line regulation	<±0.5%	<±0.5%
Full load efficiency	>80%	>80%
Inrush current	20A/115V , 40A/230V (cold start)	20A/115V , 40A/230V (cold start)
Input leakage current	<0.7mA/230VAC	<0.7mA/230VAC
Output voltage adjust range	±10%	±10%
Output overload current protection	110%~150%, current limiting, auto recovery	110%~150%, current limiting, auto recovery
Output overload voltage protection	115%~150%	115%~150%
Rise time	50ms@full load(typical)	50ms@full load(typical)
Hold-up time	20ms@full load(typical)	20ms@full load(typical)
Operating temperature & humidity	-10℃~50℃(14℉~122℉) , 20%~93%RH(non-condensing)	-10℃~50℃(14℉~122℉) , 20%~93%RH(non-condensing)
Storage temperature & humidity	-20℃~+85℃(-4℉~185℉) , 20%~95%RH(non-condensing)	-20℃~+85℃(-4℉~185℉) , 20%~95%RH(non-condensing)
Cooling method	Convection	Convection
Work environment	Indoor use, applicable for dry environment	Indoor use, applicable for dry environment
Dimension	L120 * W60 * H40 mm (L4.7 * W2.4 * H1.6 inch)	L120 * W60 * H40 mm (L4.7 * W2.4 * H1.6 inch)
Weight	320 g	320 g



ATG ELECTRONICS

ATG Electronics Corp.

628 Zhangyang Road, Suite 1-21B, Shanghai 200122, CHINA

www.atgelectronics.com E-mail: sales@atgelectronics.com

Phone: +86-21-58350166 Fax: +86-21-58351977

V5.1-110701